



(43) International Publication Date
26 May 2005 (26.05.2005)

PCT

(10) International Publication Number
WO 2005/046425 A3

(51) International Patent Classification⁷: A61M 5/178

(21) International Application Number:
PCT/IL2004/001035

(22) International Filing Date:
11 November 2004 (11.11.2004)

(25) Filing Language: English

(26) **Publication Language:** English

(30) Priority Data:
158889 16 November 2003 (16.11.2003) IL

(71) Applicant and

(72) Inventor: **POPOV, Sergey** [IL/IL]; 32/17, Alexander Yanai St., P. O. Box 4583, 84144 Beer-Sheva (IL).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,


AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:
— *with international search report*

[Continued on next page]

(54) Title: DILATING TROCAR



(57) Abstract: Dilating trocar (40) (see fig. 14) comprises cannula (42) containing carrier (51) with pivotable dilating members (49, 50) of small transversal dimensions protruding distally of the cannula. Obturator (63) is housed inside the carrier and has sharp element (70) with undersprung protective shield (71) protruding distally of the dilating members. After inserting the closed dilating members into a small opening primary made in patient's body cavity wall (60) by sharp element (70), user removes the obturator, introduces an actuating rod into carrier (51) and forces apart the dilating members rotating them about axes (52, 53) and thereby stretching the primary opening to provide the cannula insertion therein. Finally, user removes the actuating rod, carrier and dilating members from cannula (42) remaining the cannula in patient's body.



— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(88) **Date of publication of the international search report:**
15 September 2005